

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Hexane, mixture of isomers

Product Number : 439185
Brand : Sigma-Aldrich

Company : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +18003255832
Fax : +18003255052
Emergency Phone # : (314) 776-6555

2. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : Hexanes
Isohexane

Formula : C₆H₁₄

CAS-No.	EC-No.	Index-No.	Concentration
n-Hexane			
110-54-3	203-777-6	601-037-00-0	<= 65 %
Methylcyclopentane			
96-37-7	202-503-2	-	>= 10 %
Hexane isomers			
96-14-0	202-481-4	601-007-00-7	< 5 %
2-Methylpentane			
107-83-5	203-523-4	601-007-00-7	< 5 %
Hexanes, isomers			
-	-	-	>= 20 - <= 25 %

3. HAZARDS IDENTIFICATION**Emergency Overview****OSHA Hazards**

Flammable liquid, Target Organ Effect, Toxic by ingestion, Irritant, Reproductive hazard

Target Organs

Peripheral nervous system., Kidney, Testes.

HMIS Classification

Health hazard: 2
Chronic Health Hazard: *
Flammability: 3
Physical hazards: 0

NFPA Rating

Health hazard: 2
Fire: 3
Reactivity Hazard: 0

Potential Health Effects

Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause drowsiness and dizziness.
Skin May be harmful if absorbed through skin. Causes skin irritation.
Eyes Causes eye irritation.
Ingestion Toxic if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage.

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing give artificial respiration Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIRE-FIGHTING MEASURES

Flammable properties

Flash point -23 °C (-9 °F)

Ignition temperature no data available

Suitable extinguishing media

For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Special protective equipment for fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods for cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE**Handling**

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.
Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in cool place.

Moisture sensitive.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value	Control parameters	Update	Basis
n-Hexane	110-54-3	TWA	50 ppm	2007-01-01	USA. ACGIH Threshold Limit Values (TLV)
Remarks	Central Nervous System impairment Eye irritation Peripheral neuropathy Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption				
		TWA	50 ppm 180 mg/m ³	1989-01-19	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	500 ppm 1,800 mg/m ³	1997-08-04	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	The value in mg/m ³ is approximate.				
2-Methylpentane	107-83-5	TWA	500 ppm 1,800 mg/m ³	1989-03-01	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		STEL	1,000 ppm 3,600 mg/m ³	1989-03-01	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	500 ppm	1994-09-01	USA. ACGIH Threshold

			1,760 mg/m3		Limit Values (TLV)
Remarks	Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL). See CFR 58(124):36338-33351, June 30, 1993, for revised OSHA PEL.				
		STEL	1,000 ppm 3,500 mg/m3	1994-09-01	USA. ACGIH Threshold Limit Values (TLV)
	Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL). See CFR 58(124):36338-33351, June 30, 1993, for revised OSHA PEL. Substances for which there is a Biological Exposure Index or Indices (see BEI® section)				
		TWA	500 ppm	2007-01-01	USA. ACGIH Threshold Limit Values (TLV)
	Eye & Upper Respiratory Tract irritation Central Nervous System impairment				
		STEL	1,000 ppm	2007-01-01	USA. ACGIH Threshold Limit Values (TLV)
	Eye & Upper Respiratory Tract irritation Central Nervous System impairment				
		TWA	500 ppm 1,800 mg/m3	1989-01-19	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		STEL	1,000 ppm 3,600 mg/m3	1989-01-19	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
Hexane isomers	96-14-0	TWA	500 ppm 1,800 mg/m3	1989-03-01	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		STEL	1,000 ppm 3,600 mg/m3	1989-03-01	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	500 ppm 1,760 mg/m3	1994-09-01	USA. ACGIH Threshold Limit Values (TLV)
Remarks	Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL). See CFR 58(124):36338-33351, June 30, 1993, for revised OSHA PEL.				
		STEL	1,000 ppm 3,500 mg/m3	1994-09-01	USA. ACGIH Threshold Limit Values (TLV)
	Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL). See CFR 58(124):36338-33351, June 30, 1993, for revised OSHA PEL. Substances for which there is a Biological Exposure Index or Indices (see BEI® section)				
		TWA	500 ppm	2007-01-01	USA. ACGIH Threshold Limit Values (TLV)
	Eye & Upper Respiratory Tract irritation Central Nervous System impairment				

		STEL	1,000 ppm	2007-01-01	USA. ACGIH Threshold Limit Values (TLV)
Eye & Upper Respiratory Tract irritation Central Nervous System impairment					
		TWA	500 ppm 1,800 mg/m ³	1989-01-19	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		STEL	1,000 ppm 3,600 mg/m ³	1989-01-19	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves.

Eye protection

Face shield and safety glasses

Skin and body protection

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form liquid

Safety data

pH no data available
Melting point -95 °C (-139 °F)
Boiling point 68 - 70 °C (154 - 158 °F) at 1,013 hPa (760 mmHg)
Flash point -23 °C (-9 °F)
Ignition temperature no data available
Lower explosion limit 1.1 %(V)
Upper explosion limit 7.5 %(V)
Density 0.672 g/cm³
Water solubility no data available

10. STABILITY AND REACTIVITY

Storage stability

Stable under recommended storage conditions.

Conditions to avoid

Heat, flames and sparks.

Materials to avoid

Oxidizing agents, Strong oxidizing agents

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Hazardous reactions

Vapours may form explosive mixture with air.

11. TOXICOLOGICAL INFORMATION**Acute toxicity**

no data available

Irritation and corrosion

no data available

Sensitisation

no data available

Chronic exposure

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Signs and Symptoms of Exposure

Prolonged or repeated contact with skin may cause:, defatting, Dermatitis, Contact with eyes can cause:, Redness, Blurred vision, Provokes tears., Effects due to ingestion may include:, Gastrointestinal discomfort, Central nervous system depression, Lung irritation, chest pain, pulmonary edema

Potential Health Effects

Inhalation	May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause drowsiness and dizziness.
Skin	May be harmful if absorbed through skin. Causes skin irritation.
Eyes	Causes eye irritation.
Ingestion	Toxic if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage.
Target Organs	Peripheral nervous system., Kidney, Testes.,

12. ECOLOGICAL INFORMATION**Elimination information (persistence and degradability)**

no data available

Ecotoxicity effects

no data available

Further information on ecology

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS**Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION**DOT (US)**

UN-Number: 1208	Class: 3	Packing group: II
Proper shipping name: Hexanes		
Reportable Quantity (RQ): 7692 lbs		
Marine pollutant: No		
Poison Inhalation Hazard: No		

IMDG

UN-Number: 1208	Class: 3	Packing group: II	EMS-No: F-E, S-D
Proper shipping name: HEXANES			
Marine pollutant: No			

IATA

UN-Number: 1208	Class: 3	Packing group: II
Proper shipping name: Hexanes		

15. REGULATORY INFORMATION**OSHA Hazards**

Flammable liquid, Target Organ Effect, Toxic by ingestion, Irritant, Reproductive hazard

DSL Status

This product contains the following components that are not on the Canadian DSL nor NDSL lists.

Hexanes, isomers	CAS-No.
	-

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

n-Hexane	CAS-No.	Revision Date
	110-54-3	2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

n-Hexane	CAS-No.	Revision Date
	110-54-3	2007-07-01

Methylcyclopentane	96-37-7	2007-03-01
2-Methylpentane	107-83-5	1993-04-24
Hexane isomers	96-14-0	1993-04-24

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
n-Hexane	110-54-3	2007-07-01
Methylcyclopentane	96-37-7	2007-03-01
2-Methylpentane	107-83-5	1993-04-24
Hexanes, isomers	-	
Hexane isomers	96-14-0	1993-04-24

New Jersey Right To Know Components

	CAS-No.	Revision Date
n-Hexane	110-54-3	2007-07-01
Methylcyclopentane	96-37-7	2007-03-01
2-Methylpentane	107-83-5	1993-04-24
Hexanes, isomers	-	
Hexane isomers	96-14-0	1993-04-24

California Prop. 65 Components

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

16. OTHER INFORMATION

Further information

Copyright 2009 Sigma-Aldrich Co. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Co., shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.