MSDS Number: **S4586** * * * * * Effective Date: **03/14/11** * * * * * Supersedes: **09/14/09**



Material Safety Data Sheet

From: Avantor Performance Materials, Inc. Saucon Valley Plaza 3477 Corporate Parkway Suite #200 Center Valley, PA 18034





24 Hour Emergency Telephone: 908-859-2151

CHEMTREC: 1-800-424-9300

National Response in Canada CANUTEC: 613-996-6666

Outside U.S. and Canada Chemtrec: 703-527-3887

NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

All non-emergency questions should be directed to Customer Service, 1-855-AVANTOR (855-282-6867) for assistance.

SODIUM OXALATE

1. Product Identification

Synonyms: Ethandioic acid disodium salt; disodium salt oxalic acid

CAS No.: 62-76-0

Molecular Weight: 134.00

Chemical Formula: NaOCOCOONa

Product Codes: J.T. Baker: 3800, 3801

Macron: 7844

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous	
Sodium Oxalate	62-76-0	99 - 10	0% Yes	

3. Hazards Identification

Emergency Overview

POISON! DANGER! CORROSIVE. CAUSES BURNS TO ANY AREA OF CONTACT. MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY AFFECT KIDNEYS.

SAF-T-DATA(tm) Ratings (Provided here for your convenience)

Health Rating: 3 - Severe (Poison) Flammability Rating: 0 - None Reactivity Rating: 1 - Slight

Contact Rating: 4 - Extreme (Corrosive)

Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES

Storage Color Code: White (Corrosive)

Potential Health Effects

Inhalation:

Inhalation of dust is corrosive to mucous membranes. Oxalates can be absorbed through the lungs. Symptoms of poisoning include nervousness, cramps, central nervous system depression.

Ingestion:

Mean lethal dose for oxalates in adults is estimated at 15-30 grams with death within a few hours or even minutes. Corrosive action on the mucosa and severe gastrointestitis can occur with pain, vomiting, etc. Sharp reduction of serum calcium can cause disfunction of the brain. Calcium oxalate may be deposited in the kidneys.

Skin Contact:

Corrosive. Symptoms of redness, pain, and severe burn can occur.

Eye Contact:

Corrosive. Contact can cause blurred vision, redness, pain and severe tissue burns.

Chronic Exposure:

Circulatory failure or nervous system irregularities may follow prolonged calcium metabolism disturbances due to oxalation.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders or eye problems, or impaired liver, kidney or respiratory function may be more susceptible to the effects of the substance.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion:

If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact:

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eve Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Not considered to be a fire hazard.

Explosion:

Not considered to be an explosion hazard.

Fire Extinguishing Media:

Use any means suitable for extinguishing surrounding fire.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Pick up and place in a suitable container for reclamation or disposal, using a method that does not generate dust.

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

None established.

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures as low as possible. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

For conditions of use where exposure to dust or mist is apparent and engineering controls are not feasible, a particulate respirator (NIOSH type N95 or better filters) may be worn. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-face positive-pressure, air-supplied respirator.

WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear protective gloves and clean body-covering clothing.

Eye Protection:

Use chemical safety goggles. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance: White powder. Odor: Odorless. **Solubility:** 3.7g/100g water @ 20C (68F). **Specific Gravity:** 2.34 pH: Aqueous solution is neutral. % Volatiles by volume @ 21C (70F): **Boiling Point:** Not applicable. **Melting Point:** 250 - 270C (482 - 518F) Vapor Density (Air=1): No information found. Vapor Pressure (mm Hg): No information found. **Evaporation Rate (BuAc=1):**

No information found.

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

May produce acrid smoke and irritating fumes when heated to decomposition.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Strong oxidizers and strong acids.

Conditions to Avoid:

Heat, incompatibles.

11. Toxicological Information

No LD50/LC50 information found relating to normal routes of occupational exposure.

\Cancer Lists\							
Ingredient	Known	Anticipated	IARC Category				
Sodium Oxalate (62-76-0)	No	No	None				

12. Ecological Information

Environmental Fate:

No information found.

Environmental Toxicity:

No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Although not a listed RCRA hazardous waste, this material may exhibit one or more characteristics of a hazardous waste and require appropriate analysis to determine specific disposal requirements. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: TOXIC SOLID, CORROSIVE, ORGANIC, N.O.S. (SODIUM OXALATE)

Hazard Class: 6.1, 8 UN/NA: UN2928 Packing Group: II

Information reported for product/size: 2.5KG

International (Water, I.M.O.)

Proper Shipping Name: TOXIC SOLID, CORROSIVE, ORGANIC, N.O.S. (SODIUM OXALATE)

Hazard Class: 6.1, 8 UN/NA: UN2928 Packing Group: II

Information reported for product/size: 2.5KG

International (Air, I.C.A.O.)

Proper Shipping Name: TOXIC SOLID, ORGANIC, N.O.S. (SODIUM OXALATE)

Hazard Class: 6.1 UN/NA: UN2811 Packing Group: III

Information reported for product/size: 2.5KG

15. Regulatory Information

\Chemical Inventory Status - Part Ingredient	1\				 Australia	
		IJCA	LC	Japan	AUSCIACIA	
Sodium Oxalate (62-76-0)					Yes	
\Chemical Inventory Status - Part	2\					
Ingredient		Korea	DSL	anada NDSL 	Phil.	
Sodium Oxalate (62-76-0)				No		
\Federal, State & International Regulations - Part 1\						
Ingredient	RQ	TPQ	Lis	st Che	mical Catg.	
Sodium Oxalate (62-76-0)						
\Federal, State & International Regulations - Part 2\						
Ingredient	CERCL	A	261.33	3 8 	(d)	
Sodium Oxalate (62-76-0)	No			N (
nemical Weapons Convention: No TSCA 12	(b):	No	CDTA	: No		

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No SARA 311/312: Acute: Yes Chronic: Yes Fire: No Pressure: No Pressu

Reactivity: No (Pure / Solid)

Australian Hazchem Code: None allocated.

Poison Schedule: None allocated.

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: 3 Flammability: 0 Reactivity: 0

Label Hazard Warning:

POISON! DANGER! CORROSIVE. CAUSES BURNS TO ANY AREA OF CONTACT. MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY AFFECT KIDNEYS.

Label Precautions:

Do not get in eyes, on skin, or on clothing.

Avoid breathing dust. Keep container closed.

Use with adequate ventilation.

Wash thoroughly after handling.

Label First Aid:

If swallowed, give large quantities of water to drink and call a physician immediately. Never give anything by mouth to an unconscious person. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In all cases get medical attention immediately.

Product Use:

Laboratory Reagent.

Revision Information:

No Changes.

Disclaimer:

THE INFORMATION PRESENTED IN THIS MATERIAL SAFETY DATA SHEET (MSDS/SDS) WAS PREPARED BY TECHNICAL PERSONNEL BASED ON DATA THAT THEY BELIEVE IN THEIR GOOD FAITH JUDGMENT IS ACCURATE. HOWEVER, THE INFORMATION PROVIDED HEREIN IS PROVIDED "AS IS," AND AVANTOR PERFORMANCE MATERIALS MAKES AND GIVES NO REPRESENTATIONS OR WARRANTIES WHATSOEVER, AND EXPRESSLY DISCLAIMS ALL WARRANTIES REGARDING SUCH INFORMATION AND THE PRODUCT TO WHICH IT RELATES, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION, WARRANTIES OF ACCURACY, COMPLETENESS, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY, STABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, AND ANY WARRANTIES ARISING FROM COURSE OF DEALING, COURSE OF PERFORMANCE, OR USAGE OF TRADE.

THIS MSDS/SDS IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONARY HANDLING OF THE MATERIAL BY A PROPERLY TRAINED PERSON USING THIS PRODUCT, AND IS NOT INTENDED TO BE COMPREHENSIVE AS TO THE MANNER AND CONDITIONS OF USE, HANDLING, STORAGE, OR DISPOSAL OF THE PRODUCT. INDIVIDUALS RECEIVING THIS MSDS/SDS MUST ALWAYS EXERCISE THEIR OWN INDEPENDENT JUDGMENT IN DETERMINING THE APPROPRIATENESS OF SUCH ISSUES. ACCORDINGLY, AVANTOR PERFORMANCE MATERIALS ASSUMES NO LIABILITY WHATSOEVER FOR THE USE OF OR RELIANCE UPON THIS INFORMATION. NO SUGGESTIONS FOR USE ARE INTENDED AS, AND NOTHING HEREIN SHALL BE CONSTRUED AS, A RECOMMENDATION TO INFRINGE ANY EXISTING PATENTS OR TO VIOLATE ANY FEDERAL, STATE, LOCAL, OR FOREIGN LAWS. AVANTOR PERFORMANCE MATERIALS REMINDS YOU THAT IT IS YOUR LEGAL DUTY TO MAKE ALL INFORMATION IN THIS MSDS/SDS AVAILABLE TO YOUR EMPLOYEES.

Prepared by: Environmental Health & Safety