# SIGMA-ALDRICH

sigma-aldrich.com

## SAFETY DATA SHEET

Version 4.6 Revision Date 02/28/2015 Print Date 08/20/2015

### 1. PRODUCT AND COMPANY IDENTIFICATION

1.1	<b>Product identifiers</b> Product name	:	Barium hydroxide
	Product Number Brand Index-No.	::	433373 Aldrich 056-002-00-7
	CAS-No.	:	17194-00-2
1.2	I.2 Relevant identified uses of the substance or mixture and uses advised aga		e substance or mixture and uses advised against
	Identified uses	:	Laboratory chemicals, Manufacture of substances
1.3	1.3 Details of the supplier of the safety data sheet		safety data sheet
	Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
	Telephone Fax	:	+1 800-325-5832 +1 800-325-5052
1.4	Emergency telephone nur	nbe	er

#### Emergency Phone # : (314) 776-6555

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS) Acute toxicity, Oral (Category 4), H302 Skin corrosion (Category 1A), H314 Serious eye damage (Category 1), H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word	Danger
Hazard statement(s) H302 H314 H318	Harmful if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage.
Precautionary statement(s) P260 P264 P270	Do not breathe dust or mist. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.

P301 + P330 + P331 P303 + P361 + P353	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

Formula	:	H <sub>2</sub> BaO <sub>2</sub>
Molecular weight	:	171.34 g/mol
CAS-No.	:	17194-00-2
EC-No.	:	241-234-5
Index-No.	:	056-002-00-7

### Hazardous components

Component	Classification	Concentration
Barium hydroxide		
	Acute Tox. 4; Skin Corr. 1A;	<= 100 %
	Eye Dam. 1; H302, H314,	
	H318	
	H318	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.Continue rinsing eyes during transport to hospital.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

- 5.2 Special hazards arising from the substance or mixture Barium oxide
- **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.
- 5.4 Further information No data available

### 6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.
- 6.2 Environmental precautions Do not let product enter drains.
- 6.3 Methods and materials for containment and cleaning up Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.
- 6.4 Reference to other sections For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Air sensitive. Keep in a dry place. Storage class (TRGS 510): Non-combustible, corrosive hazardous materials

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis
			parameters	
Barium hydroxide	17194-00-2	TWA	0.500000	USA. Occupational Exposure Limits
-			mg/m3	(OSHA) - Table Z-1 Limits for Air
			U U U U U U U U U U U U U U U U U U U	Contaminants
		TWA	0.500000	USA. ACGIH Threshold Limit Values
			mg/m3	(TLV)
	Remarks	Eye irritation		
		Muscular stir	mulation	
		Skin irritatior	۱	
		Gastrointesti	inal irritation	
		Not classifial	ble as a human ca	rcinogen

TWA	0.500000	USA. NIOSH Recommended
	mg/m3	Exposure Limits

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### **Eye/face protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Do not let product enter drains.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: powder Colour: white
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	12.5 at 50 g/l at 20 °C (68 °F)
e)	Melting point/freezing point	Melting point/range: > 300 °C (> 572 °F) - lit.
f)	Initial boiling point and boiling range	No data available

g)	Flash point	Not applicable
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	2.2 g/mL at 25 °C (77 °F)
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	No data available
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Oth	er safety information	
	Bulk density	0.90 - 1.10 g/l

#### **10. STABILITY AND REACTIVITY**

### 10.1 Reactivity

9.2

No data available

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5** Incompatible materials acids, Strong oxidizing agents
- **10.6 Hazardous decomposition products** Other decomposition products - No data available In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity LD50 Oral - Rat - 308 mg/kg

Dermal: No data available

No data available

#### Skin corrosion/irritation Causes skin burns.

#### Serious eye damage/eye irritation

Risk of serious damage to eyes.

#### Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

No data available

No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

#### **Aspiration hazard** Corrosive to the respiratory tract.

## Additional Information

RTECS: CQ9200000

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., Cough, Shortness of breath, Headache, Nausea

Stomach - Irregularities - Based on Human Evidence

### **12. ECOLOGICAL INFORMATION**

12.1 Toxicity

No data available

- 12.2 Persistence and degradability No data available
- **12.3 Bioaccumulative potential** No data available

#### 12.4 Mobility in soil No data available

12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

May be harmful to aquatic organisms due to the shift of the pH.

No data available

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Dispose of as unused product.

#### 14. TRANSPORT INFORMATION

#### DOT (US)

UN number: 3262 Class: 8 Packing group: II Proper shipping name: Corrosive solid, basic, inorganic, n.o.s. (Barium hydroxide) Reportable Quantity (RQ):

Poison Inhalation Hazard: No

#### IMDG

UN number: 3262 Class: 8 Packing group: II EMS-No: F-A, S-B Proper shipping name: CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (Barium hydroxide)

#### IATA

UN number: 3262 Class: 8 Packing group: II Proper shipping name: Corrosive solid, basic, inorganic, n.o.s. (Barium hydroxide)

#### 15. REGULATORY INFORMATION

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Barium hydroxide	17194-00-2	2007-07-01

#### SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

#### **Massachusetts Right To Know Components**

No components are subject to the Massachusetts Right to Know Act.

#### Pennsylvania Right To Know Components

Barium hydroxide	CAS-No. 17194-00-2	Revision Date 2007-07-01
New Jersey Right To Know Components	- · - · ·	
Barium hydroxide	CAS-No. 17194-00-2	Revision Date 2007-07-01

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

Acute Tox.	Acute toxicity
Eye Dam.	Serious eye damage
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
Skin Corr.	Skin corrosion
HMIS Rating	
Health hazard:	3
Chronic Health Haz	zard: *
Flammability:	0

Physical Hazard	0
NFPA Rating	
Health hazard:	3
Fire Hazard	0

0

### Fire Hazard: Reactivity Hazard:

#### Further information

Copyright 2015 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 4.6

Revision Date: 02/28/2015

Print Date: 08/20/2015