



Oxygen, compressed

Safety Data Sheet P-4638

Making our planet more productive™ according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Date of Issue: 01/01/1979 Revision date: 06/23/0015 Supersedes: 05/11/2015

SECTION 1: Product and company identification

- 1.1. Product identifier**
- : Substance
 - : Oxygen, compressed
 - : 7782-44-7
 - : O2
- Other means of identification**
- : Oxygen, Compressed; MedPure Oxygen; Aviator's Breathing Oxygen; USP Oxygen; Oxygen - Diving Grade

1.2. Relevant identified uses of the substance or mixture and uses advised against

- Use of the substance/mixture
- : Medical applications.
 - : Industrial use
 - : Diving Gas (Underwater Breathing)

1.3. Details of the supplier of the safety data sheet

Praxair, Inc.
39 Old Ridgebury Road
Danbury, CT 06810-5113 - USA
T 1-800-772-9247 (1-800-PRAXAIR) - F 1-716-879-2146
WWW.PRAXAIR.COM

- 1.4. Emergency telephone number**
- : Onsite Emergency: 1-800-645-4633

CHEMREC, 24hr/day 7days/week — Within USA: 1-800-424-9300, Outside USA: 001-703-527-3887 (collect calls accepted, Contract 17729)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)
Ox. Gas 1
Compressed gas

2.2. Label elements

GHS-US labelling
Hazard pictograms (GHS-US)



- Signal word (GHS-US)
DANGER
- Hazard statements (GHS-US)
H270 - MAY CAUSE OR INTENSIFY FIRE, OXIDIZER
H280 - CONTAINS GAS UNDER PRESSURE, MAY EXPLODE IF HEATED
- Precautionary statements (GHS-US)
P202 - Do not handle until all safety precautions have been read and understood
P244 - Keep reduction valves/valves and fittings free from oil and grease
P271+P283 - Use and store only outdoors or in a well-ventilated place.
P280 - Wear eye protection
P281 - In case of leak, stop flow and close valve slowly.
CGA-PG05 - Use each fire protection device for piping.
CGA-PG20+CGA-PG10 - Use only with equipment of compatible materials of construction and rated for cylinder pressure.
CGA-PG22 - Use only with equipment cleaned for oxygen service.
CGA-PG21 - Open valve slowly.
CGA-PG06 - Close valve after each use and when empty.
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

EN (English US)

SDS ID: P-4638

1/9

This document is only controlled while on the Praxair, Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



Oxygen, compressed

Safety Data Sheet P-4638

Making our planet more productive™ according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Date of Issue: 01/01/1979 Revision date: 06/23/0015 Supersedes: 05/11/2015

2.3. Other hazards

Other hazards not contributing to the classification

- : Breathing 80 percent or more oxygen at atmospheric pressure for more than a few hours may cause nasal stuffiness, cough, sore throat, chest pain, and breathing difficulty. Breathing oxygen at higher pressure increases the likelihood of adverse effects within a shorter time period. Breathing pure oxygen under pressure may cause lung damage and central nervous system (CNS) effects, including convulsions, dizziness, and loss of consciousness and hearing disturbances, muscular twitching, unconsciousness, and convulsions. Breathing oxygen under pressure may cause prolongation of adaptation to darkness and reduced peripheral vision.

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Name : Oxygen, compressed
CAS No : 7782-44-7

Name	Product Identifier	%
Oxygen	(CAS No) 7782-44-7	99.5 - 100

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

- : First-aid measures after inhalation
- : First-aid measures after skin contact
- : First-aid measures after eye contact
- : First-aid measures after ingestion
- : Most important symptoms and effects, both acute and delayed
- : No additional information available

4.2. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

- : Vigorously accelerates combustion. Use media appropriate for surrounding fire. Water (e.g., safety shower) is the preferred extinguishing media for clothing fires.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Oxidizing agent; vigorously accelerates combustion. Contact with flammable materials may cause fire or explosion.

5.3. Advice for firefighters

Firefighting instructions

- : High-pressure, oxidizing gas.
- : Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.
- : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.

EN (English US)

SDS ID: P-4638

2/9

This document is only controlled while on the Praxair, Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



Oxygen, compressed

Safety Data Sheet P-4638

according to U.S. Code of Federal Regulations 29 CFR 1910.1200. Hazard Communication.
Date of Issue: 01/01/1979 Revision date: 06/23/0015 Supersedes: 05/11/2015

Specific methods

- Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas containers to rupture. Cool endangered containers with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.

Stop flow of product if safe to do so.

Use water spray or fog to knock down fire flumes if possible.

- Heat of fire can build pressure in container and cause it to rupture. Containers are equipped with a pressure relief device. (Exceptions may exist where authorized by DOT.) No part of the container should be subjected to a temperature higher than 125°F (52°C). Smoking, flames, and electric sparks in the presence of enriched oxygen atmospheres are potential explosion hazards.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Ensure adequate air ventilation. Eliminate ignition sources. Evacuate area. Try to stop release. Monitor concentration or released product. Wear self-contained breathing apparatus when entering area unless atmosphere is proven to be safe. Stop leak if safe to do so.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.
- The suitability of this product as a component in underwater breathing gas mixtures is to be determined by or under the supervision of personnel experienced in the use of underwater breathing gas mixtures and familiar with the physiological effects, methods employed, frequency and duration of use, hazards, side effects, and precautions to be taken.

Safe use of the product



Oxygen, compressed

Safety Data Sheet P-4638

according to U.S. Code of Federal Regulations 29 CFR 1910.1200. Hazard Communication.
Date of Issue: 01/01/1979 Revision date: 06/23/0015 Supersedes: 05/11/2015

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

- Store only where temperature will not exceed 125°F (52°C). Post "No Smoking or Open Flames" signs in storage and use areas. There must be no sources of ignition. Separate packages and protect against potential fire and/or explosion damage following appropriate codes and requirements (e.g., NFPA 30, NFPA 55, NFPA 70, and/or NFPA 221 in the U.S.) or according to requirements determined by the Authority Having Jurisdiction (AHJ). Always secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand when the container is not in use. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. For other precautions in using this product, see section 16.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Oxygen, compressed (7782-44-7)	Not established
ACGIH	Not established
USA OSHA	Not established
Oxygen (7782-44-7)	Not established
ACGIH	Not established
USA OSHA	Not established

8.2. Exposure controls

- Appropriate engineering controls
- Avoid oxygen rich (>23.5%) atmospheres. Use a local exhaust system with sufficient flow velocity to maintain an adequate supply of air in the worker's breathing zone. Mechanical (general): General exhaust ventilation may be acceptable if it can maintain an adequate supply of air.

Eye protection

Skin and body protection

- Wear safety glasses with side shields.
- Wear metatarsal shoes and work gloves for cylinder handling, and protective clothing where needed. Wear appropriate chemical gloves during cylinder changeout or wherever contact with product is possible. Select per OSHA 29 CFR 1910.132, 1910.136, and 1910.138.

As needed for welding, wear hand, head, and body protection to help prevent injury from radiation and sparks. (See ANSI Z49.1.) At a minimum, this includes welder's gloves and protective goggles, and may include arm protectors, aprons, hats, and shoulder protection as well as substantial clothing.

Respiratory protection

- When workplace conditions warrant respirator use, follow a respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure (e.g., an organic vapor cartridge). For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Appearance

- Gas
- Colorless gas.

EN (English US)

SDS ID: P-4638

39

49

Oxygen, compressed
Safety Data Sheet P-4638

Making our planet more productive™ according to U.S. Code of Federal Regulations 29 CFR 1910.1200. Hazard Communication.
Date of Issue: 01/01/1979 Revision date: 06/23/0015 Supersedes: 05/11/2015

Molecular mass	: 32 g/mol
Color	: Colorless.
Odor	: No odor warning properties.
Odor threshold	: No data available
pH	: Not applicable.
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable.
Melting point	: -219 °C (-362°F)
Freezing point	: No data available
Boiling point	: -183 °C (-297°F)
Flash point	: Not applicable.
Critical temperature	: -118.6 °C (-181.48°F)
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: Not applicable.
Critical pressure	: 50.4 bar (731.4 psia)
Relative vapor density at 20 °C	: 0.0827 lb/lb (1.325 kg/m ³) absolute vapor density at 70°F/21.1°C, 1 atm
Relative density	: 1.1
Density	: 1.4289 kg/m ³ (at 21.1 °C)
Relative gas density	: 1.1
Solubility	: Water: 39 mg/l
Log Pow	: Not applicable.
Log Kow	: Not applicable.
Viscosity, kinematic	: Not applicable.
Viscosity, dynamic	: Not applicable.
Explosive properties	: Not applicable.
Oxidizing properties	: Oxidizer.
Explosion limits	: No data available
9.2. Other information	: Compressed gas
Gas group	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.
Additional information	

SECTION 10: Stability and reactivity

10.1. Reactivity	No additional information available
10.2. Chemical stability	Stable under normal conditions.
10.3. Possibility of hazardous reactions	Violently oxidizes organic material.
10.4. Conditions to avoid	None under recommended storage and handling conditions (see section 7).
10.5. Incompatible materials	Keep equipment free from oil and greases. Consider the potential toxicity hazard due to the presence of hydrocarbons or fluorinated hydrocarbons in high pressure oxygen. Hydrocarbons may react with oxygen during combustion. May react violently with combustible materials. May react violently with reducing agents.

EN (English US) SDS ID: P-4638 5/9

This document is only controlled while on the Praxair, Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

Oxygen, compressed
Safety Data Sheet P-4638

Making our planet more productive™ according to U.S. Code of Federal Regulations 29 CFR 1910.1200. Hazard Communication.
Date of Issue: 01/01/1979 Revision date: 06/23/0015 Supersedes: 05/11/2015

10.6. Hazardous decomposition products	None.
SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity	Ecology - general	: No ecological damage caused by this product.
12.2. Persistence and degradability	Oxygen, compressed (7782-44-7) Persistence and degradability	No ecological damage caused by this product.
	Oxygen (7782-44-7) Persistence and degradability	No ecological damage caused by this product.
12.3. Bioaccumulative potential	Oxygen, compressed (7782-44-7) Log Pow	Not applicable.
	Log Kow	Not applicable.
	Bioaccumulative potential	No ecological damage caused by this product.
	Oxygen (7782-44-7) Log Pow	Not applicable.
	Log Kow	Not applicable.
	Bioaccumulative potential	No ecological damage caused by this product.
12.4. Mobility in soil	Oxygen, compressed (7782-44-7) Mobility in soil	No data available.
	Ecology - soil	No ecological damage caused by this product.
	Oxygen (7782-44-7) Mobility in soil	No data available.
	Ecology - soil	No ecological damage caused by this product.
12.5. Other adverse effects	Effect on ozone layer	: None.
	Effect on the global warming	: No known effects from this product.

EN (English US) SDS ID: P-4638 6/9

This document is only controlled while on the Praxair, Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



Oxygen, compressed

Safety Data Sheet P-4638

Making our planet more productive® according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Date of Issue: 01/01/1979 Revision date: 06/23/0015 Supersedes: 05/11/2015

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

SECTION 14: Transport information

In accordance with DOT

- Transport document description : UN1072 Oxygen, compressed, 2.2
- UN-No.(DOT) : UN1072
- Proper Shipping Name (DOT) : Oxygen, compressed
- Transport hazard class(es) (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas, 49 CFR 173.115
- Hazard labels (DOT) : 2.2 - Non-flammable gas
5.1 - Oxidizer



DOT Special Provisions (49 CFR 172.102) : 110 - Fire extinguishers transported under UN1044 may include installed actuating cartridges (cartridges, power device of Division 1.4C or 1.4S), without changing the classification of Division 2.2, provided the aggregate quantity of delagrating (propellant) explosives does not exceed 3.2 grams per extinguishing unit.
A14 - This material is not authorized to be transported as a limited quantity or consumer commodity in accordance with 173.306 of this subchapter when transported aboard an aircraft.

Additional information

Emergency Response Guide (ERG) Number : 122 (UN1072)

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Transport by sea

- UN-No. (IMDG) : 1072
- Proper Shipping Name (IMDG) : OXYGEN, COMPRESSED
- Class (IMDG) : 2 - Gases
- MFAG-No : 122

Air transport

- UN-No.(IATA) : 1072
- Proper Shipping Name (IATA) : Oxygen, compressed
- Class (IATA) : 2
- Civil Aeronautics Law : Gases under pressure/Gases nonflammable nontoxic under pressure

SECTION 15: Regulatory information

15.1. US Federal regulations

Oxygen, compressed (7782-44-7)

SAARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Fire hazard
--------------------------------------	--

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory.

EN (English US)

SDS ID: P-4638

7/9

This document is only controlled while on the Praxair, Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



Oxygen, compressed

Safety Data Sheet P-4638

Making our planet more productive® according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Date of Issue: 01/01/1979 Revision date: 06/23/0015 Supersedes: 05/11/2015

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(g) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Oxygen, compressed (7782-44-7)	Listed on the Canadian DSL (Domestic Substances List)
Oxygen (7782-44-7)	Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Oxygen, compressed (7782-44-7)	Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
--------------------------------	--

15.2.2. National regulations

Oxygen, compressed (7782-44-7)	Listed on the AICS (Australian Inventory of Chemical Substances)
Oxygen, compressed (7782-44-7)	Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Oxygen, compressed (7782-44-7)	Listed on the Korean ECL (Existing Chemicals List)
Oxygen, compressed (7782-44-7)	Listed on NZIoC (New Zealand Inventory of Chemicals)
Oxygen, compressed (7782-44-7)	Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

Oxygen, compressed(7782-44-7)	U.S. - California - Proposition 65 - Carcinogens List	No
Oxygen, compressed(7782-44-7)	U.S. - California - Proposition 65 - Developmental Toxicity	No
Oxygen, compressed(7782-44-7)	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
Oxygen, compressed(7782-44-7)	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
Oxygen, compressed(7782-44-7)	State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

Oxygen (7782-44-7)	U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Oxygen (7782-44-7)	No	No	No	No

Oxygen (7782-44-7)	U.S. - Massachusetts - Right To Know List	U.S. - New Jersey - Right to Know Hazardous Substance List	U.S. - Pennsylvania - RTK (Right to Know) List
--------------------	---	--	--

SECTION 16: Other information

Revision date : 6/23/0015 12:00:00 AM

EN (English US)

SDS ID: P-4638

8/9

This document is only controlled while on the Praxair, Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



Oxygen, compressed

Safety Data Sheet P-4638

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of Issue: 01/01/1979 Revision date: 06/23/0015 Supersedes: 05/11/2015

Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Praxair asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair SDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Praxair sales representative, local distributor, or supplier, or download from www.praxair.com. If you have questions regarding Praxair SDSs, would like the document number and date of the latest SDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (Phone: 1-800-PRAXAIR/1-800-772-9247; Address: Praxair Call Center, Praxair, Inc., P.O. Box 44, Tonawanda, NY 14151-0044).

PRAXAIR and the Flowing Airstream design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.

NFPA health hazard

NFPA fire hazard

NFPA reactivity

NFPA specific hazard



- : 0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.
- : 0 - Materials that will not burn.
- : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
- : OX - This denotes an oxidizer, a chemical which can greatly increase the rate of combustion fire.

HMIS II Rating

Health

Flammability

Physical

: 0 Minimal Hazard - No significant risk to health

: 0 Minimal Hazard

: 3 Serious Hazard

SDS US (GHS HazCom 2012) - Praxair

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.