

MATERIAL SAFETY DATA SHEET

PRISM LIQUID METAL POLISH

PRODUCT/MATERIAL: PRISM POLISH
MANUFACTURER: PRISM PRODUCTS, INC.
42W534 EMPIRE ROAD
ST. CHARLES, IL. 60175
TELEPHONE NUMBER: 877-377-5112 8:30AM-5:00PM CST
EMERGENCY NUMBER: CHEMTREC (24 HOURS A DAY)
800-424-9300

SECTION I - PRODUCT IDENTIFICATION

PRODUCT CODE
PRODUCT DESCRIPTION METAL POLISH AND FIBERGLASS CLEANER

SECTION II - HAZARDOUS INGREDIENTS

<u>INGREDIENT NAME</u>	<u>CAS NUMBER</u>	<u>APPROXIMATE %</u>
Petroleum Distillates	64742-47-8	<20
Ammonium Hydroxide	1336-21-6	

SECTION III - HAZARDS IDENTIFICATION

EYE CONTACT: PASTE CAUSES EYE IRRITATION
SKIN CONTACT: PROLONGED OR REPEATED CONTACT MAY RESULT IN SKIN IRRITATION
INHALATION: VAPORS MAY CAUSE IRRITATION TO NOSE, THROAT, AND RESPIRATORY TRACT
INGESTION: INGESTION OF PRODUCT MAY RESULT IN VOMITING

SECTION IV - FIRST AID MEASURES

EYES: FLUSH EYES WITH PLENTY OF WATER WHILE HOLDING EYELIDS OPEN
SKIN: REMOVE CONTAMINATED CLOTHING. FLUSH SKIN WITH WATER FOLLOWED BY WASHING WITH SOAP AND WATER. IF IRRITATION OCCURS, GET MEDICAL ATTENTION. DO NOT REUSE CLOTHING UNTIL CLEANED.
INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN OR APPLY ARTIFICIAL RESPIRATION IF NEEDED.
INGESTION: IF SWALLOWED, CONSULT A PHYSICIAN IMMEDIATELY.

SECTION V - FIRE AND EXPLOSION DATA

FLASH POINT (PENSKEY-MARTENS CLOSED CUP) 178 DEG F
EXPLOSIVE LIMITS
LOWER: NOT DETERMINED
UPPER: NOT DETERMINED
EXTINGUISHING MEDIA: DRY CHEMICAL, CARBON DIOXIDE, FOAM, OR WATER FOG. CLASS BC, ABC FIRE EXTINGUISHER
SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED POSITIVE PRESSURE BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN

SECTION VI - ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK PROCEDURES: CONTAIN ALL SPILLS AND LEAKS TO PREVENT DISCHARGE INTO THE ENVIRONMENT. SOAK UP WITH AN ABSORBENT, SHOVEL INTO A WASTE CONTAINER.
WASTE DISPOSAL: RECOVER MATERIAL OR DISPOSE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION VII - HANDLING AND STORAGE

HANDLING: ENSURE GOOD VENTILATION AT THE WORKPLACE.
STORAGE: KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. BEST IF STORED IN DRY, COOL PLACE - AWAY FROM EXCESSIVE HEAT AND FREEZING.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION: NOT NORMALLY NECESSARY WHEN USED IN A VENTILATED AREA, BUT IF EXPOSURE IS SIGNIFICANT A NIOSH APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE.
PROTECTIVE CLOTHING: COVERALLS
PROTECTION OF HANDS: IMPERVIOUS GLOVES
EYE PROTECTION: SAFETY GOGGLES OR FACE SHIELD

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT	201 DEG F
SOLUBILITY IN WATER	DISPERSIBLE
SPECIFIC GRAVITY (H2O=1)	1.12 @ 25 DEG F
EVAPORATION RATE (BUTYL ACETATE=1)	<1
VAPOR PRESSURE (mm Hg)	UNKNOWN
MELTING POINT	N/A
VAPOR DENSITY (AIR=1)	<1
ODOR	MILD
APPEARANCE	MAUVE PASTE

SECTION X - STABILITY AND REACTIVITY

STABILITY: STABLE
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
INCOMPATIBILITY: STRONG OXIDIZING AGENTS
HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE

SECTION XI - TOXOLOGICAL INFORMATION

THERE ARE NO KNOWN DANGEROUS ACUTE OR CHRONIC EFFECTS ASSOCIATED WITH THE USE OF THIS MATERIAL.

SECTION XII - ECOLOGICAL INFORMATION

NO HARMFUL AFFECTS KNOWN.

SECTION XIII - DISPOSAL CONSIDERATIONS

IF THIS PRODUCT BECOMES A WASTE, IT WOULD NOT BE A HAZARDOUS WASTE BY RCRA CRITERIA (40 CFR 261). DISPOSE IN COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION XIV - TRANSPORTATION INFORMATION

FREIGHT SHIPPING CLASS: 55
NMFC #: 33440

U.S. DOT: NOT REGULATED

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY.
CERCLA HAZARDOUS MATERIALS: NONE

SECTION XVI - OTHER INFORMATION

THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, MP PROS, INC. MAKES NO WARRANTY; EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. MP PROS, INC. ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.

ISSUED: 1/04
msdsas04